

Stalwart Safety Stalwart Safety Stalwart Safety Stalwart Safety Stalwart Safety Stalwart Safety Stalwart alwart Safety Stalwart Safety Stalwart Safety Stalwart Safety afety Stalwart Safety Stalwart Safety Stalwart Safety Stalwart afety Stalwart Safety Stalwart Safety Stalwart Safety Stalwart Stalwart Safety Stalwart ety Stalwart Safety Stalwart Safety Stalwart Safety Stalwart Staet

# ANSI Cut Level A4 HPPE-Glass Core **Blend Nitrile Foam Blast Coated Glove**

#### Application

Construction, Metal Fabrication & Stamping, HVAC, Recycling, Aerospace/Automotive Manufacturing, Glass Handling and many other material handling applications requiring high cut resistance in oily environments.

#### Description

- HPPE-Glass Core yarns provide high cut and abrasion levels.
- Seamless knit fully protects hands while maintaining comfort and good dexterity.
- Black Nitrile Foam Blast coating provides good grip in oily environments.
- Open breathable knit back of hand provides additional comfort.

## **Product Code: 455NB**

### **Technical Data**

- ANSI CUT LEVEL A4
- ASTM F2992-15 1816g
- EN388 Abrasion 4
- EN388 Cut 5
- EN388 Tear 4
- EN388 Puncture 4

## Construction

- Shell Aramid-Stainless Steel Composite • Yarn, Nylon Plait Yarn, 13 Gauge Knit
- Wrist Integrated Knit Wrist
- Thumb Ambidextrous Knit w/Right & Left Hands Formed Due to Coating
- Coating Nitrile Foam Blast

### **Care Guidelines**

Launder in warm water (40oC/104oF) using mild detergent, tumble dry at moderate temperature (60oC/140oF). Do not use bleach or oxidizers.

### Packaging

- 12 PR/Polybag
- 72 PR/Carton



#### Sizes





STALWART SAFETY | 1010 University Ave. W. Windsor ON | www.stalwartsafety.com Phone: 844.945.5050 | Fax: 519.968.9707 | insidesales@stalwartsafety.com