



Stalwart Safety

ANSI Cut Level A2 Aramid-Nylon Blend Polyurethane Coated Glove

Application

Construction, Metal Fabrication & Stamping, HVAC, Recycling, Aerospace/Automotive Manufacturing, Glass Handling and many other material handling applications requiring cut resistance.

Description

- Aramid-Nylon fiber yarns provide good cut and abrasion levels.
- Seamless knit fully protects hands while maintaining comfort and good dexterity.
- Grey polyurethane coating provides addition abrasion resistance and grip.
- Open breathable knit back of hand provides additional comfort.

Product Code: 210A

Technical Data

- ANSI CUT LEVEL A2
- ASTM F2992-15 – 835g
- EN388 Abrasion – 4
- EN388 Cut – 4
- EN388 Tear – 4
- EN388 Puncture – 3

Construction

- Shell – Aramid, Nylon Plait Yarn
- Coating – Polyurethane

Care Guidelines

Launder in warm water (40°C/104°F) using mild detergent, tumble dry at moderate temperature (60°C/140°F). Do not use bleach or oxidizers.

Packaging

- 12 PR/Polybag
- 72 PR/Carton



Sizes

Size	6	7	8	9	10	11
Fit	X-Small	Small	Medium	Large	X-Large	2XL

