



# Stalwart Safety

## ANSI Cut Level A2 HPPE-Nylon Polyurethane Coated Glove

### Application

Assembly Line Production, Construction, Masonry, Metal Stamping, HVAC, Material Handling, Recycling, Automotive Manufacturing, Glass Handling and many other material handling applications requiring cut and abrasion resistance.

### Description

- HPPE-Nylon yarns provide high cut and abrasion levels
- Seamless knit construction fully protects hands while maintaining comfort and dexterity
- Grey Polyurethane coating provides additional abrasion resistance and grip
- Open breathable knit back for added comfort

## Product Code: 195

### Technical Data

- ANSI Cut Level: A2
- ASTM F2992-15: 563g
- EN388 Abrasion: 4
- EN388 Cut: 3
- EN388 Tear: 4
- EN388 Puncture: 2

### Construction

- Shell: HPPE Nylon plait knit, 13 gauge knit
- Coating: Polyurethane
- Wrist: Integrated knit wrist
- Thumb: Ambidextrous, right/left formed due to coating

### Care Guidelines

Launder in warm water (40°C/104°F) using mild detergent, tumble dry at low temperature (60°C/140°F).

### Packaging

- 12 pair/polybag
- 72 pair/carton



### Sizes

Size	6	7	8	9	10	11
Fit	X-Small	Small	Medium	Large	X-Large	2XL



**STALWART SAFETY** | 1010 University Ave. W. Windsor ON | [www.stalwartsafety.com](http://www.stalwartsafety.com)  
Phone: 844.945.5050 | Fax: 519.968.9707 | [insidesales@stalwartsafety.com](mailto:insidesales@stalwartsafety.com)